

Mobile safety storage box

**WA940101****WA940102**

A large number of production tools are needed on production sites or in factories, such as large electric welding machines, pipe wrench, hammers and other tools. Smaller tools such as adjustable wrench, spanner, screwdriver, etc. The disorder of these tools caused by the negligence of production workers may results in relatively messy at the construction site. In addition to this, the flow of personnel at the construction site or other construction situation is relatively large, which may lead to the problem of safe storage of tools.

The general approach is basically to store your own tools, but for some common tools it may be a case of poor management for some reason.

SYSBEL's mobile safe storage box can prevent these situations from happening.

1. Anti-theft and prying-resistant. The unique design of embedded safety lock can effectively prevent the lock from being prized, thereby preventing the tools inside the box from being stolen.
2. Anti-rust. High-quality industrial coating can prevent the product from rusting in the open air.
3. A reinforced head cover. Reinforce the head cover of the box to prevent it from being pried open.
4. Fine welding. Enables the product structure so that the product structure can be more stable..
5. A pneumatic support frame. Make it easy to open the box.
6. The color is bright and easy to find.
7. Embedded side handle. Easy to move.
8. The applicability is wide. It not only can be used in factories, construction sites and other places and can also be loaded into trucks for transportation.

Mobile safety storage box

Product	Material	Colour	External dimension (Length X Width X Height/mm)	Package size (Length X Width X Height/mm)	Net weight (kg)	Gross weight (kg)	Model
Mobile safety storage box	Hot-rolled cold-rolled steel	Yellow	1219×610×699	1250×640×720	68.5	71.6	WA940101
Mobile safety storage box	Hot-rolled cold-rolled steel	Yellow	1219×764×850.5	1250×790×875	82.8	86	WA940102

Caster (optional)

In the absence of track tools such as forklifts, casters can be equipped to move the carriage of truck. The basic dimensions of casters are as follows:

Product	Material	Installation height (cm)	Baseplate size (cm)	Installation pitch-row (cm)	Aperture (mm)	Bearing (kg)	Remarks
Caster	Polyurethane	16.5	11.5*10	7.2*8.5	8.5	350	Equipped with 16 sets of M8X12 bolts and M8 locknuts

Equipped with four casters, two of them are universal wheels for brake, the other two caster are directional wheels. It's easy to be fixed after moving. The total bearing is 0.9 tons.

universal wheels
for brakedirectional
wheels

The padlock (optional)

To equip padlock for the mobile safety storage box. With the prying-resistant design of the mobile safety storage box, the safety of the storage tool in the carriage of truck can be further ensured. The basic parameters of the padlock are as follows:

Product	Material	High inside the chain (mm)	Lock rod diameter (mm)	Lock body diameter (mm)	Colour	Model
Padlock	Metal	38 ± 2	6	45	Red	SCL001

